



| | MULTISTRADA V2 | MULTISTRADA V2 S |
|---|--|---|
| ENGINE | | |
| TYPE | Ducati Testastretta, L-Twin cylinder, Desmodromic timing, 4 valves per cylinder, Liquid cooled | Ducati Testastretta, L-Twin cylinder, Desmodromic timing, 4 valves per cylinder, Liquid cooled |
| DISPLACEMENT | 937 cc (57.2 cu in) | 937 cc (57.2 cu in) |
| BORE X STROKE | 94 x 67.5 mm | 94 x 67.5 mm |
| COMPRESSION RATIO | 12.6:1 | 12.6:1 |
| POWER | 113 hp (83 kW) @ 9,000 rpm | 113 hp (83 kW) @ 9,000 rpm |
| TORQUE | 96 Nm (9.8 kgm, 71 lb ft) @ 7,750 rpm 94 Nm (9.6 kgm, 69 lb ft) @ 6,750 rpm* | 96 Nm (9.8 kgm, 71 lb ft) @ 7,750 rpm 94 Nm (9.6 kgm, 69 lb ft) @ 6,750 rpm* |
| FUEL INJECTION | Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system | Electronic fuel injection system, Ø 53 mm throttle bodies with Ride-by-Wire system |
| EXHAUST | Stainless steel single muffler, Catalytic converter and 2 lambda probes | Stainless steel single muffler, Catalytic converter and 2 lambda probes |
| TRANSMISSION | | |
| GEARBOX | 6 speed | 6 speed with Ducati Quick Shift up/down (DQS) |
| PRIMARY DRIVE | Straight cut gears; Ratio 1.84:1 | Straight cut gears; Ratio 1.84:1 |
| RATIO | 1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24 | 1=37/15, 2=30/17, 3=28/20, 4=26/22, 5=24/23, 6=23/24 |
| FINAL DRIVE | Chain; Front sprocket 15; Rear sprocket 43 | Chain; Front sprocket 15; Rear sprocket 43 |
| CLUTCH | Slipper and self-servo wet multiplate clutch with hydraulic control | Slipper and self-servo wet multiplate clutch with hydraulic control |
| CHASSIS | | |
| FRAME | Tubular steel trellis frame | Tubular steel trellis frame |
| FRONT SUSPENSION | Ø 48 mm fully adjustable usd fork | Ø 48 mm fully adjustable usd fork, Electronic compression and rebound damping adjustment with Ducati Skyhook Suspension Evo |
| FRONT WHEEL | Light alloy casted 3.0" x 19" | Light alloy casted 3.0" x 19" |
| FRONT TYRE | Pirelli Scorpion Trail II 120/70 ZR 19 | Pirelli Scorpion Trail II 120/70 ZR 19 |
| REAR SUSPENSION | Fully adjustable monoshock, Remote spring preload adjustment, Aluminium double-sided swingarm | Fully adjustable monoshock, Electronic compression, rebound damping and spring pre-load adjustment with Ducati Skyhook Suspension Evo, Aluminium double-sided swingarm |
| REAR WHEEL | Light alloy casted 4.5" x 17" | Light alloy casted 4.5" x 17" |
| REAR TYRE | Pirelli Scorpion Trail II 170/60 ZR 17 | Pirelli Scorpion Trail II 170/60 ZR 17 |
| WHEEL TRAVEL (FRONT/REAR) | 170 mm / 170 mm (6.7 in / 6.7 in) | 170 mm / 170 mm (6.7 in / 6.7 in) |
| FRONT BRAKE | 2 x Ø 320 mm aluminum flange semi-floating discs, Radially mounted Brembo monobloc 4-piston 2-pad callipers, Radial Master Cylinder, Cornering ABS | 2 x Ø 320 mm aluminum flange semi-floating discs, Radially mounted Brembo monobloc 4-piston 2-pad callipers, Radial Master Cylinder, Cornering ABS |
| REAR BRAKE | Ø 265 mm disc, 2-piston Brembo floating calliper, Cornering ABS | Ø 265 mm disc, 2-piston Brembo floating calliper, Cornering ABS |
| INSTRUMENTATION | LCD Display | 5" TFT colour display |
| DIMENSIONS AND WEIGHTS | | |
| DRY WEIGHT | 199 kg (439 lb) | 202 kg (445 lb) |
| KERB WEIGHT* | 222 kg (489 lb) | 225 kg (496 lb) |
| SEAT HEIGHT | 830 mm (32.7 in) (850 mm (33.5 in) with high seat accessory, 810 mm (31.9 in) with low seat accessory, 790 mm (31.1 in) with low seat + low suspension kit accessory) | 830 mm (32.7 in) (850 mm (33.5 in) with high seat accessory, 810 mm (31.9 in) with low seat accessory, 790 mm (31.1 in) with low seat + low suspension kit accessory) |
| WHEELBASE | 1,594 mm (62.8 in) | 1,594 mm (62.8 in) |
| RAKE | 25° | 25° |
| TRAIL | 106 mm (4.2 in) | 106 mm (4.2 in) |
| FUEL TANK CAPACITY | 20 l (5.3 US Gal) | 20 l (5.3 US Gal) |
| NUMBER OF SEATS | Dual seat | Dual seat |
| EQUIPMENT | | |
| SAFETY EQUIPMENT | Riding Modes, Power Modes, Ducati Safety Pack (Cornering ABS, Ducati Traction Control), Ducati Brake Light, Vehicle Hold Control | Riding Modes, Power Modes, Ducati Safety Pack (Cornering ABS, Ducati Traction Control), Ducati Cornering Lights, Ducati Brake Light, Vehicle Hold Control |
| STANDARD EQUIPMENT | Self cancelling turn indicators | Ducati Skyhook Suspension Evo, Ducati Quick Shift up/down, Cruise control, Hands-Free, Backlit handlebar switches, 5" TFT colour display, Full LED headlight, Self cancelling turn indicators |
| READY FOR | Ducati Quick Shift up/down, Ducati Multimedia System, Antitheft system | Ducati Multimedia System, Tyre Pressure Monitoring System, Antitheft system |
| WARRANTY AND MAINTENANCE | | |
| WARRANTY | 24/48** months, Unlimited mileage | 24/48** months, Unlimited mileage |
| MAINTENANCE SERVICE INTERVALS | 15,000 km (9,000 miles) / 12 months | 15,000 km (9,000 miles) / 12 months |
| DESMOSERVICE | 30,000 km (18,000 miles) | 30,000 km (18,000 miles) |
| EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies) | | |
| STANDARD | Euro 5 | Euro 5 |
| CO2 EMISSIONS | 137 g/km | 137 g/km |
| CONSUMPTION | 5.9 l/100km | 5.9 l/100km |

* Only for countries where Euro 5 standard applies

** Only for countries where 4ever Multistrada warranty applies